

Generated: 03/06/2026 07:26

Titan 41000 4K-UHD (Preliminary)



Brightness: 41,000 ISO / 36,000 ANSI @ 4K-UHD. 45,000 ISO / 42,000 ANSI @ WUXGA | Contrast: 18,000:1 (Dynamic Black)



TECHNICAL CONFIGURATION

Brightness:	41,000 ISO / 36,000 ANSI @ 4K-UHD. 45,000 ISO / 42,000 ANSI @ WUXGA
Contrast:	18,000:1 (Dynamic Black) / 2,000:1 Native
Colour System:	Laser Phosphor with ColorBoost+Red Laser
Computer Compatability:	2D 4K-UHD up to 60Hz 3D Supported Formats will be displayed up to WUXGA
Mechanical Mounting:	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet
Dimensions:	L: 840mm, W: 650mm, H: 381mm (Excl handles) L: 33.1in, W: 25.6in, H: 15in (Excl handles) * See drawings for full details
Bandwidth:	18Gb/s (600MHz clock rate) on HDMI
Lamp Type:	Laser Light Source
Typical Lamp Life:	20,000 Hours (Normal Mode) 40,000 Hours (ECO Mode)
Colour Temperature:	3200K to 9300K
HDTV Formats:	1080p (23.98Hz, 24Hz, 25Hz, 29.97Hz, 30Hz, 50Hz, 59.94Hz, 60Hz). 1080i (50Hz, 59.94Hz, 60Hz).

720p (50Hz, 59.94Hz, 60Hz).
 4K-UHD (23.97Hz, 24Hz, 25Hz, 29.97Hz, 30Hz, 50Hz, 60Hz).

Remote Control:	Addressable IR remote Control, Wireless and wired. On-Board keypad
Automation Control:	LAN RS-232 Alert E-Mails from Projector Served webpage OSD functions for full Projector Control via web browser LAN Control-Crestron Roomview™ LAN Control-Crestron eControl LAN Control-PJ Link compatible LAN Control-AMX SSDP LAN to RS232 (RS232 by Telnet) Concurrence Control for RS232/LAN DMX Art-Net control Scheduled On and Off times
Temperature:	Operating: Full Power 0°C ~ 35°C (32°F ~95°F), ECO upto 40°C (104°F) Storage: -20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity:	Operating: 10% ~ 90% non-condensing Storage: 10% ~ 90% non-condensing
Fan Noise:	Max 54 dBA Eco Typ : 53 dBA (TBC)
Power Requirements:	110V~130Vac/ 50~60Hz 180V~240Vac/ 50~60Hz single phase * Note that in 120V operation, the projector will be at ~25% brightness
Power Consumption:	230V Typical: 3650W , Maximum 4000W
Thermal Dissipation:	Max 14160.38 BTU/hr @ 200VAC Max 3685 BTU/hr @ 110VAC
Safety:	TBC
Product url:	https://www.axiondisplays.com/brands/digital-projection/projectors/titan/titan-laser-41000-4k/
3D Compatibility:	Sequential / 1080P/WUXGA @100Hz Sequential / 1080P/WUXGA @120Hz Dual-Pipe / 101080P/WUXGA80p @ 50Hz per eye Dual-Pipe / 1080P/WUXGA @ 60Hz per eye Also supports mandatory formats including side by side, top/bottom and frame packing
Source Compatibility:	2D Graphics standards up to 4K-UHD 3840x2160 resolution at 60Hz via HDMI 2.0b, HDBaseT (4:2:0), DisplayPort inputs 3D Graphics standards up to dual-pipe WUXGA 60Hz for input (120Hz output) via HDMI 2.0 and Display Port inputs 12G-SDI is SMPTE 259M, 292M, 424M and ST-2082 compliant. WUXGA mode 2D sources up to WUXGA 60Hz and 4K-UHD 60Hz can be displayed scaled to fit

WUXGA

3D sources up to WUXGA 60Hz Input -120Hz output can be displayed scaled to fit WUXGA

4K-UHD mode

2D sources up to 4K (4096 x 2160) will be displayed scaled to fit 4K-UHD

Auto Mode

Sources greater than WUXGA will be displayed scaled to fit 4K-UHD

Video Processing:

Video & Graphics Processing

- HDMI 2.0 compliance for Side by Side, Frame Packing, Frame Sequential and TopBottom 3D Formats.
- DisplayPort 1.2 with HDCP 2.2 compliance.
- 10-bit colour processing (30-bits per pixel).
- Support for 1080p 24Hz native display.
- Support for 4K 4096 x 2160 resolution.
- HDR support
- Input source automatically detected.
- Input redundancy mode with auto switching.
- Dual Pipe Processing: Two sources in parallel for Left and Right eyes.
- Synchronisation of active 3D glasses or polarising switcher.
- DICOM simulation mode.
- Sealed light engine

General Features

- Constant Brightness control
- Multi Projector brightness and colour control.
- Compatible with selected 3rd party lenses via lens converter
- Selectable EDID
- Custom Start-up Logo
- Smear Reduction (fast frame) (2D Only)
- Electronic PIC MUTE with selectable fade in/out timers
- On board 4 -line LCD display for at a glance status

Geometry Correction

- Vertical & Horizontal Keystone correction.
- Four Corner adjustment.
- Rotation.
- Pin/Barrel.
- Wall Corner adjustment.
- Centre Shift (Horizontal and Vertical linearity adjustment).
- Custom Warp.
- Upload of maps for warp, blend, uniformity and masking.
- Selectable aspect ratios: 5:4 / 4:3 / 16:10 /16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled.
- Digital Zoom.

- Blanking control for custom input window sizing.

Edge Blending

- Blending control available for all sides with width control.
- Correction for non-active pixels at the edge of the display.
- Electronic Black Level Compensation.
- Upload of Blend Maps including Blend, Uniformity, Masking, Pixel by Pixel

HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable
- Allows projector to be placed up to 100m from source with low cost cabling
- Supports up to 4K 4096 x 2160@60Hz 4:2:0 or 4K 4096 x 2160@30Hz 4:2:2
- Includes Ethernet 100BaseT and RS232/IR control.

Colour Processing

- Four colour modes available
- Powerful seven point colour correction for accurate colour matching with presets.
- Easy colour temperature selection
- Manual seven point colour adjustment
- Traditional lifts and gains

Projector Controller Software

- Intuitive user interface for network control
- Simultaneous control of user-defined groups of projectors
- At-a-glance monitoring of projector status

Projector Automation

- Real-time clock provides daily on/off automation
- E-mail alerts for system status

Installation

- 4 x eye bolts fitted for easy rigging.
- 4 x top stacking mounts and mount securing pins supplied as standard accessories.

Display Type:	3 x 0.96" WUXGA DMD™
Orientation:	Pointing Up: Yes Pointing Down: Yes Roll Portrait: Yes Tabletop Inverted: Yes
Lens Mount:	Motorised Shift, Zoom and Focus. Intelligent Lens Memory with 10 user-definable pre-set positions for zoom lenses.
Weight:	kg: 88 (without lens) lb: 194 (without lens)
DMD Specification:	Display capability up to 4K-UHD 8.3 megapixels on screen at 4K-UHD Fast transit pixels for smooth greyscale and improved contrast. Display capability up to 4K-UHD (3840x2160)

Fill Factor: N/A as Smooth Picture DMD

Inputs / Outputs

Input	Connector	Qty
DisplayPort 1.2a (2D)	DisplayPort	2
HDMI 2.0b	HDMI	2
12G-SDI in	BNC	1
12G-SDI out	BNC	1
HDBaseT/LAN	RJ45	1

Communication and Control

Connection	Connector	Qty
3D SYNC IN	BNC	1
3D Sync Out	BNC	1
LAN	RJ45	1
RS-232	9-pin D-Sub	1
Wired Remote	3.5mm Stereo Jack	1
12V Trigger	3.5mm Stereo Jack	1
3D Sync IR Out	BNC	1
USB 5V 2A	Type A	1

Available Lenses

Lens Name	Part #	Focus Range	Lens Shift
0.37:1 (Right Angled)	120-510	1.6m - 4.9m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.31 (L) 0.31 (R) frame
0.65-0.85:1 (Right Angled)	120-511	2.8m - 8.4m	Vert: 0.62 (U) 0.62 (D) frame, Hor: 0.25 (L) 0.25 (R) frame
0.8-1.16:1 (Includes support bracket)	120-827	1.7m - 11m	Vert: 0.51 (U) 0.51 (D) frame, Hor: 0.20 (L) 0.20 (R) frame
1.16 - 1.49:1 zoom HB	109-236	3m - 15m	Vert: 0.50 (U) 0.408 (D) frame, Hor: 0.2 (L) 0.2 (R) frame
1.39 - 1.87:1 zoom HB	105-610	4m - 24m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame
1.87 - 2.56:1 zoom HB	105-611	4m - 24m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame
2.56 - 4.16:1 zoom HB	105-612	9.1m - 45m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame
4.16 - 6.96:1 zoom HB	105-613	12m - 80m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame
6.92 - 10.36:1 zoom HB	109-235	12m - 80m	Vert: 0.65 (U) 0.45 (D) frame, Hor: 0.28 (L) 0.28 (R) frame

CONTACT US FOR A QUOTE

Email: sales@axiondisplays.com | Phone: +49 172 5390360

Web: www.axiondisplays.com | Address: Axion Displays GmbH, Kammweg 80/1, 72762 Reutlingen, Germany

Specifications are subject to change without notice. All values are typical.

Actual product appearance, colors, and features may vary.