Generated: 22/11/2026 17:12

E-Vision 6320 WU

Brightness: 6,300 ISO / 5,600 ANSI | Contrast: 3,000,000:1 (Dynamic Black) | Part Number: 124-447



TECHNICAL CONFIGURATION

Prodname:	E-Vision 6320 WU
Brightness:	6,300 ISO / 5,600 ANSI
Contrast:	3,000,000:1 (Dynamic Black)
Colour System:	Laser-Phosphor mit Farbrad
Computer Compatability:	VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, WSXGA+, Full HD, UXGA, WSXGA+, WUXGA, 4K-UHD
Mechanical Mounting:	Front/Rear TableFront/Rear Ceiling2 x adjustable feetCeiling Mount compatible chassis with 4 o M6 mounting holes available (Maximum screwlength 10mm)
Dimensions:	L: 38.0 cm x W: 49.6 cm x H: 16.0 cmL: 14.9 in x W: 19.5 in x H: 6.2 in
Bandwidth:	498 Megapixel pro Sekunde per DisplayPort und HDMI 2.0.
Lamp Type:	Laser
Typical Lamp Life:	30.000 Stunden
Colour Temperature:	User selectable (Warm / Normal / Cold)
ThreeD Formats:	Auto Top & Bottom Frame Sequential Frame Packing Side by Side DLP Link or IR Sync Output

HDTV Formats:	EDTV (480p)HDTV (720p, 1080i, 1080p)4K-UHD (3840 x 2160) signal support
Remote Control:	Infrared Remote Control Unit
Automation Control:	LAN - Webpage control TCP/UDP control via protocol commands RS-232 Alert Mail for Projector LAN Control - Crestron Connected LAN Control - Extron LAN Control-PJ Link Class 1 compatible LAN Control-AMX Device Discovery SSDP Onboard constant Brightness control
Temperature:	Fonctionnement : 5 à 40°C (41 à 104°F) Lagerung : -10 à 60°C (14 à 140°F)
Operating Humidity:	10 bis 85 % nicht kondensierend
Fan Noise:	35 dB / 31dB (TBD)
Power Requirements:	100-130 VAC und 200-240 VAC auswählbar, 50/60 Hz einphasig
Power Consumption:	950 W bei 220 Vac (1000 W bei 110 Vac) W
Thermal Dissipation:	Max. 3139 BTU/Stunde bei 100 VAC Max. 3002 BTU/Stunde bei 240 VAC BTU/Stunde
Safety:	CE, FCC Class A, ,C-Tick, CCC, CB, KC/KCC, CEL, CECP, BIS, PSB, BSMI, cTUVus, RoHS
Product url:	https://www.axiondisplays.com/brands/digital-projection/projectors/e-vision/e-vision-6320-wu/
Display resolution:	1920 x 1200
3D Compatibility:	Auto Top & Bottom Frame Sequential Frame Packing Side by Side DLP Link or IR Sync Output
Source Compatibility:	Graphics standards including WUXGA 1920 x 1200 - 120Hz RB and support up to 3840 x 2160 60Hz HDTV video standards HDTV 720p 50/60Hz, 1080p 50/60Hz Support for up to 4K-UHD (3840 x 2160) 50/60Hz
Video Processing:	**Video & Graphics Processing** • HDMI 2.0 (HDCP2.3) • Hue, Saturation and Gain colour management • Texas Instruments BrilliantColor processing • 2 x HDMI 2.0. • 3840 x 2160 24Hz and 1080p 50/60Hz display support • HDR 10 support • Input source automaticaly detected • Selectable Dynamic Black

	• DICOM simulation mode • Golf mode • Optics engine sealed to IP6X **Geometry Correction** • Vertical & Horizontal Keystone correction • Four Corner adjustment • Selectable aspect ratios: 4:3 / 16:9 / Letter Box / 21:9 / 16:10 / Auto • Blanking (Masking) control for custom input window sizing • Scaling for xed aspect ratio screens.16:9 / 16:10 / 4:3 / 21.9:1 **HDBaseT® Interface** • Optional HDBaseT® Board - DHS-01 • Has support for transmission of uncompressed High Denition Video over standard CAT5e/6 LAN cable. • Allows the projector to be placed up to 100m from the source with low cost cabling. • HDBaseT® Includes Ethernet 100BaseT and RS232/IR control. **Colour Processing** • Powerful seven point colour correction for accurate colour matching **Projector LAN Controller Software** • Free Digital Projection Projector Controller II software • Intuitive user interface for network control. • At-a-glance monitoring of projector status. • Simultaneous control of user-dened groups of projectors. **Projector Automation** • Graphics standards including WUXGA 1920 x 1200 - 120Hz RB and support up to 3840 x 2160 60Hz • HDTV video standards HDTV 720p 50/60Hz, 1080p 50/60Hz • Support for up to 4K-UHD (3840 x 2160) 50/60Hz
Display Type:	1 x 0.67" VPS DMD™
Orientation:	Pointing Up: Yes Pointing Down: Yes Roll Portrait: Yes Tabletop Inverted: Yes
Lens Mount:	Manueller Fokus und Zoom
Weight:	13 kg (28.7 lb)

Inputs / Outputs

Input	Connector	Qty
HDMI 2.0 (HDCP 2.3 compatible)	HDMI	2
HDMI Out	HDMI	1
3D Sync Out	3-Pin Din	1
HDBaseT (Optional)	8P8C "RJ45"	1
Wi-Fi for screen sharing	(Optional)	1
Audio Out	3.5mm Mini Jack	1

Input	Connector	Qty
Internal Speaker	Yes (10W)	1

Communication and Control

Connection	Connector	Qty
LAN	RJ45	1
Serial RS-232C In	9-Pin D-Sub	1
USB Power out 5V/2.0A	USB Type A	1

Available Lenses

Lens Name	Part #	Focus Range	V-Shift	H-Shift
0.5:1	N/A	0.972m - 1.757m	V: +95% ~ +109% H: ±2%	

CONTACT US FOR A QUOTE
Email: sales@axiondisplays.com | Phone: +49 172 5390360
Web: www.axiondisplays.com | Address: Axion Displays GmbH, Kammweg 80/1, 72762 Reutlingen, Germany

Specifications are subject to change without notice. All values are typical. Actual product appearance, colors, and features may vary.