

Generated: 01/09/2026 16:47

E-Vision 24000i WU



Brightness: 23,750 ISO / 21,000 ANSI | Contrast: 20,000:1 (Dynamic Black) | Part Number: 124-359



TECHNICAL CONFIGURATION

Brightness:	23,750 ISO / 21,000 ANSI
Contrast:	20,000:1 (Dynamic Black)
Colour System:	Laser Phosphor with Colorboost (Red Laser). Phosphor wheel: 2 x 7200rpm (120Hz) Colour wheel: 4 Segment RGBY 2 x 7200rpm (120Hz)
Computer Compatability:	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA up to 60hz RB, Mac
Mechanical Mounting:	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet Ceiling Mount compatible chassis with 6 off M4*0.7 mounting holes available, Maximum screw length 16mm
Dimensions:	L: 598mm x W: 500mm x H:218mm L: 23.54 inch x W: 19.68 inch x H: 8.58 inch
Lamp Type:	Laser Phosphor. ECO mode support (80% Brightness)
Typical Lamp Life:	20,000 hours
Colour Temperature:	User selectable (3200K/ 5400K / 6500K / 7500K / 9300K / Native)
HDTV Formats:	EDTV (480p, 576p), HDTV (720p, 1080i, 1080p), Display Support for 3840 x 2160 (4K-UHD) up to 60Hz and 4096 x 2160 (4K) up to 60Hz
Remote Control:	Infrared Remote Control Unit

Automation Control:	LAN - Webpage control TCP/UDP control RS-232 Alert Mail for Projector LAN Control-Crestron® Connected LAN Control-PJ Link Class 1 compatible LAN Control-AMX® Device Discovery Art-Net (DMX) control
Temperature:	Operating: 0 to 40 °C (32 to 104 °F) Force ECO over 35°C (95°F)
Operating Humidity:	90% (with maximum temperature of 35°C (95°F))
Fan Noise:	Typical 44dB, max 46dB in Normal mode / typical 39dB, max 41dB in ECO mode
Power Requirements:	110-240 VAC 11.0A 50/60Hz
Power Consumption:	At 110VAC - typical 1100 W, max 1200 W in Normal mode At 110VAC - typical 900 W, max 1000 W in High Altitude mode At 220VAC - typical 1300 W, max 1400 W in Normal mode At 220VAC - typical 900 W, max 1000 W in Eco mode At 220VAC - typical 900 W, max 1000 W in High Altitude mode
Thermal Dissipation:	At 110 VAC: typical 3576 BTU/hr, max 4097 BTU/hr in Normal mode At 110 VAC: typical 3073 BTU/hr, max 3415 BTU/hr in High Altitude mode At 220 VAC: typical 4438 BTU/hr, max 4780 BTU/hr in Normal mode At 220 VAC: typical 3073 BTU/hr, max 3415 BTU/hr in ECO mode At 220 VAC: typical 3073 BTU/hr, max 3415 BTU/hr in High Altitude mode
Safety:	cTUVus, CB report, CCC (China), CECP (China Energy Conservation Program), China RoHS, FCC part 15 Class A, FDA 21 CFR part 1040 (Except with respect to those characteristics authorised by Variance Number 2021-V-0192, CE (European Economic Area), UKCA (United Kingdom), KC (Korea), BSMI (Taiwan), RCM (Australia), IEC 60825-1 : 2014 - Class 1 Laser Product, IEC EN 62471-5:2015 - Risk Group 2 This projector may become Risk Group 3 when an interchangeable lens with a throw ratio of greater than 1.94:1 is installed Such combinations of projector and lens are intended for professional use only and are not intended for consumer use.
3D Compatibility:	Off Auto Side by Side Top and Bottom Dual Pipe Frame Sequential
Source Compatibility:	Graphics standards up to WQXGA 2560 x 1600 60 Hz RB (DisplayPort). Display Support for 3840 x 2160 (4K-UHD) up to 60Hz and 4096 x 2160 (4K) up to 60Hz.
Video Processing:	Video & Graphics Processing

- Nexus electronics platform
- HDMI 2.0
- DisplayPort 1.2
- 10-bit colour processing (30-bits per pixel) 1,073,741,824 colours
- Hue, Saturation and Gain colour management.
- 24p and 1080p native display.
- HDR support
- Input source automatically detected
- Selectable Dynamic Black
- Synchronisation of active glasses or polarising switcher.
- DICOM simulation mode
- Optics engine sealed to IP6X

Geometry Correction

- Vertical & Horizontal Keystone correction
- Four Corner adjustment
- Rotation -100 to +100 with +/- 0.25° per step
- Selectable aspect ratios: 5:4 / 4:3 / 16:10 / 16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled
- Digital Zoom 0% ~ 100%
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens. 16:10 / 16:9 / 4:3 / 2.35:1
- Custom warp

Edge Blending

- Correction for non-active pixels at the edge of the display.

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.
- HDBaseT® Includes Ethernet 100BaseT and RS232/IR control.

Colour Processing

- Powerful seven point colour correction for accurate colour matching.

Projector LAN Control

- Free Digital Projection Projector Controller II software
- Intuitive user interface for network control.
- At-a-glance monitoring of projector status.
- Simultaneous control of user-defined groups of projectors.

Display Type:	1 x 0.8" HEP DMD™ (High Efficiency Pixel)
Orientation:	Pointing Up: Yes Pointing Down: Yes Roll Portrait: Yes Tabletop Inverted: Yes
Lens Mount:	Centred lens for installation flexibility

Motorised and programmable shift, zoom and focus.
Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).

Weight:	kg: 30 lb: 66.1
DMD Specification:	1920 x 1200 pixels native display. Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	WUXGA

Inputs / Outputs

Input	Connector	Qty
HDMI 2.0 (HDCP compatible)	HDMI	2
DisplayPort 1.2	DisplayPort	2
HDBaseT	8P8C "RJ45"	1
3G-SDI in	BNC	1
3G-SDI out	BNC	1

Communication and Control

Connection	Connector	Qty
3D Sync In	BNC	1
3D Sync Out (loop through)	BNC	1
3D Sync Out for IR	BNC	1
LAN / Art-Net	EtherCON RJ45	1
HDBaseT/Ethernet/RS232/IR	RJ45	1
Serial In RS-232C	9-pin D-Sub	1
Serial Out RS-232C	9-pin D-Sub	1
Wired Remote In	3.5mm Stereo Jack	1
Wired Remote Out	3.5mm Stereo Jack	1
12V Trigger 12V 350mA	3.5mm Stereo Jack	1
USB Power out 5V/2A	USB Type A	1

Available Lenses

Lens Name	Part #	Focus Range	Lens Shift
0.31 - 0.33 :1 UST zoom (90° Type)	124-318	TBD	Vert: 0.5 (U) 0.5 (D) frame, Hor: None (L) None (R) frame
0.55 - 0.75 :1 zoom	124-319	2.03m - 7.62m	Vert: 0.5 (U) 0.5 (D) frame, Hor: 0.15 (L) 0.15 (R) frame
0.74 - 1.08 :1 zoom	124-320	1.52m - 10.16m (mech 1.27m - 12.7m)	Vert: 0.5 (U) 0.5 (D) frame, Hor: 0.15 (L) 0.15 (R) frame
1.05 - 1.41 :1 zoom	124-321	1.52m - 12.7m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.2 (L) 0.2 (R) frame
1.4 - 2.11 :1 zoom	124-322	1.52m - 12.7m (mech 1.27m - 15.24m)	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.2 (L) 0.2 (R) frame
2.1 - 4.0 :1 zoom	124-323	1.52m - 12.7m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.2 (L) 0.2 (R) frame
3.9 - 7.0:1 zoom	124-446	4.30m - 90.57m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.2 (L) 0.2 (R) frame

CONTACT US FOR A QUOTE

Email: sales@axiondisplays.com | Phone: +49 172 5390360

Web: www.axiondisplays.com | Address: Axion Displays GmbH, Kammweg 80/1, 72762 Reutlingen, Germany

Specifications are subject to change without notice. All values are typical.

Actual product appearance, colors, and features may vary.